



Clevis Socket Fitting for Braided Jacket Kevlar Rope

Electroline synthetic rope fittings for Kevlar rope with braided jackets excel in meeting the need for a quick, reliable end termination. These fittings use a swageless design with an internal taper pin that allows them to be installed in the field without special tools or complicated processes. They are selected for both the rope size and rated rope strength.

- Available for ropes 3/16 to 3/4" in size.
- Machined from aluminum to provide lightweight strength.

Specifications

Termination Type	Swageless
Connector Type	Clevis
Jacket Type	Braided
Rope Material	Kevlar Rope
Material	Aluminum

Available Products

Rope Size (In.)	Part No.	Rated Breaking Strength (lbs.)	Dimensions (In.)					
			A	B	C	D	E	F
3/16	IKA-118	2400 to 4400	1/2	57/64	5-11/16	1	3/8	3/8
1/4	IKA-125	4400 to 6000	19/32	59/64	6-3/4	1-1/8	3/8	7/16
5/16	IKA-131	6000 to 9000	21/32	1-5/64	7-9/16	1-1/2	7/16	1/2
3/8	IKA-137	9000 to 13000	21/32	1-5/64	8-9/16	1-1/2	7/16	1/2
1/2	IKA-150	16000 to 22000	27/32	1-1/4	11-1/2	1-3/4	5/8	11/16
5/8	IKA-162	28000 to 37000	1-15/64	1-27/32	14-11/32	2-1/2	3/4	1-1/8
3/4	IKA-175	35000 to 63000	1-3/4	2-1/4	16-3/4	3	15/16	1-3/8