



SYNTHETIC ROPE

Eye Socket Fitting for Braided Jacket Kevlar Rope

Designed for Kevlar ropes with a braided jacket, this fitting features an eye connector and a swageless termination that allows the fitting to be quickly installed in the field without special tools or processes.

- Available for ropes 3/16 to 3/4" in size.
- Machined from aluminum to provide lightweight strength.

Specifications

Termination Type	Swageless
Connector Type	Eye
Jacket Type	Braided
Rope Material	Kevlar Rope
Material	Aluminum

Available Products

Rope Size (In.)	Part No.	Rated Breaking Strength (lbs.)	Dimensions (In.)					
			A	B	C	D	E	F
3/16	IKA-218	2400 to 4400	1/2	13/16	5-9/16	1	23/64	25/64
1/4	IKA-225	4400 to 6000	19/32	27/32	6-7/8	1-1/8	23/64	29/64
5/16	IKA-231	6000 to 9000	21/32	31/32	7-15/16	1-1/2	27/64	33/64
3/8	IKA-237	9000 to 13000	21/32	1-1/16	8-15/16	1-1/2	31/64	41/64
1/2	IKA-250	16000 to 22000	27/32	1-3/8	11-1/4	1-3/4	3/4	61/64
5/8	IKA-262	28000 to 37000	1-1/2	2	14-3/4	2-1/2	1-1/4	1-5/32
3/4	IKA-275	35000 to 63000	2	2-1/2	17-1/4	3	1-3/8	1-13/32