




## Eye & Eye Pressure Compensated Swivel - Model SSP-66



Electroline's Model SSP-66 industrial sub-surface swivel is designed for underwater marine applications and features two eye-end fittings. Constructed from stainless steel, the oil-filled housing is sealed and pressure compensated to prevent water entry.

- Angular contact bearings support higher rotational speeds and longer rope lengths.
- Tapered ends are designed to prevent snags on other equipment or cables.
- Ultimate strength exceeds the rated Working Load Limit (WLL).

### Specifications

Material	Stainless Steel
Termination Type	Eye
Connector Type	Eye
Water Pressure Resistance	High

### Available Products

Part No.	WLL 3:1 (Pounds)	WLL 5:1 (Pounds)	Dimensions (In.)					Overall Length
			A	E	H	J - Hole Dia.	K	
SSP-6625	5,000	3,000	1-1/4	5/16	1/2	3/8	7/16	5
SSP-6637	8,000	4,800	1-1/2	1/2	23/32	5/8	5/8	5-5/8
SSP-6650	11,500	6,900	1-7/8	3/4	15/16	7/8	15/16	7-3/4
SSP-6662	18,500	11,100	2-7/16	1	1-5/16	1-1/4	1-3/16	11-3/8
SSP-6675	31,500	18,900	3-1/4	1-1/4	1-5/8	1-3/8	1-1/2	13-7/16
SSP-6687	33,333	20,000	3-5/8	1-1/2	2-27/32	1-1/2	1-13/16	17-1/2
SSP-6699	50,000	30,000	3-5/8	2	2-25/32	2	2-1/8	18-7/8